

Product Data Sheet

**NP 6693 (E 8/2 U0/U5 HACCP
white FDA)**

Applications

Bakery industry	Cutting devices and stamping devices for dough
------------------------	--

Order information

Article number	906693
Suitable for corrugated side walls	Yes
Standard delivery width	3100 mm / 122.05 in
Longitudinal seam possible	Yes

Construction

Top face material	Polyurethane
Surface pattern	Smooth
Coating thickness	0.5 mm / 0.02 in
Color	White
Driving face material	Polyurethane impregnation
Surface pattern	Fabric
Color	Transparent
Tension member material	Laterally stiff fabric of polyester warp and weft
Number of fabric plies	2
Driving face weave	Plain weave

NP 6693 (E 8/2 U0/U5 HACCP white FDA)

Technical data

Total thickness	1.6 mm ± 0.15 0.063 in ± 0.006
Weight	1.7 kg/m ² ± 0.15 0.348 lbs/ft ² ± 0.031
k1% value relaxed (effective pull at 1% elongation), established in line with ISO 21181:2005	6 N/mm / 34.26 lbf/in
Recommended Elongation at fitting min.	0.3 %
Recommended Elongation at fitting max.	1 %
Friction coefficient of driving face against steel panel according ISO 21182	0.15
Permissible operating temperature	-30/100 °C, for a short time 120 °C -22/212 °F, for a short time 248 °F
Hardness of top face coating as per DIN 53505 (Shore A)	85

Properties

Lateral stiffness	Laterally stiff
Troughable	No
Suitable for accumulation	No
Inclined conveying	No
Suitable for knife edges	Yes
Suitable for curves	No
Flame-retardant	No
Noise development	Normal
Coating/fabric exceptionally cut resistant	Yes
Belt support	Slider bed (support rollers possible)

Obsolet - deleted from product range

NP 6693 (E 8/2 U0/U5 HACCP white FDA)

Food properties

(EU) 10/2011 and (EC) 1935/2004	Suitable for the transport of unpacked Food in compliance with food safety regulation (EU) 10/2011 and regulation (EC) 1935/2004
FDA 21CFR	Suitable for the transport of unpacked Food in compliance with FDA regulation 21CFR
Halal	Certificated Halal product. Meets trade description order 2011 and CODEX Alimentarius 1997 guidelines under supervision of Islamic Food Research Centre Hong Kong & Asia Region
HACCP	Special design that supports the HACCP concept; resistant to hot water; ideal for frequent cleaning cycles.

Electrostatic properties

Antistatic	Belt material with an electrically conductive antistatic agent. Volume resistance (RDi) in longitudinal direction parallel to plane of belt $< 3 \times 10^8 \Omega$. Measurement according DIN EN ISO 21178.
-------------------	--

Fabrication

Belt edge sealing	Smartseal
Suitable for corrugated side walls	Yes
Profiles on top face	Yes
Profiles on underside	Yes
Mechanical fasteners	KS

Minimum drum diameter

Z-splice, counter-bending	24 mm / 0.9 in
Z-splice, minimum radius fixed knife edge	5 mm / 0.2 in

Remarks

Chemical resistance	U
----------------------------	---

Obsolet - deleted from product range

NP 6693 (E 8/2 U0/U5 HACCP white FDA)

The physical data in this data sheet is approximate, can alter depending on production environments and was established at standard ambient conditions (23°C/73°F, 50% relative humidity) in accordance with DIN 50014/ISO 554. Fluctuations in climate can cause variations. See our brochure "Technical Information 1" no. 317 which shows the types of belts that can be supplied and the manufacturing tolerances. Customised types require written confirmation.

Date of last change: 9/19/2020 6:47:08 AM

Obsolet - deleted from product range