

Product Data Sheet

E 12/2 0/V6 MT-C-SE black



Applications

Airport logistics	Luggage transport behind check-in
General material handling	Curved belt
Logistics	Accumulation conveyor; Parcel handling

Order information

Article number	906882
Suitable for corrugated side walls	No
Standard delivery width	3350 mm / 131.89 in
Longitudinal seam possible	On request

Construction

Top face material	Polyvinyl chloride
Surface pattern	Matt
Coating thickness	0.6 mm / 0.024 in
Color	Black
Driving face material	Polyester fabric
Surface pattern	Fabric
Color	Transparent
Tension member material	Laterally flexible fabric of polyester warp and weft
Number of fabric plies	2
Driving face weave	Plain weave

E 12/2 0/V6 MT-C-SE black

Technical data

Total thickness	2.1 mm ± 0.1 0.083 in ± 0.004
Weight	2.5 kg/m ² ± 0.1 0.512 lbs/ft ² ± 0.02
k1% value relaxed (effective pull at 1% elongation), established in line with ISO 21181:2005	3 N/mm / 17.13 lbf/in
Recommended Elongation at fitting min.	0.3 %
Recommended Elongation at fitting max.	1 %
Friction coefficient of driving face against steel panel according ISO 21182	0.17
Permissible operating temperature	-10/70 °C 14/158 °F
Hardness of top face coating as per DIN 53505 (Shore A)	63

Properties

Lateral stiffness	Laterally flexible
Troughable	Yes
Suitable for accumulation	Yes
Inclined conveying	No
Suitable for knife edges	No
Suitable for curves	Yes
Flame-retardant	Flame-retardant according to EN 20340/ISO 340 and ASTM 378-D
Noise development	Normal
Belt support	Slider bed (support rollers possible)

Electrostatic properties

Antistatic	Belt material with an electrically conductive antistatic agent. Volume resistance (RDi) in longitudinal direction parallel to plane of belt < 3 x 10 ⁸ Ω. Measurement according DIN EN ISO 21178.
-------------------	--

E 12/2 0/V6 MT-C-SE black

Fabrication

Belt edge sealing	On request
Suitable for corrugated side walls	No
Profiles on top face	Yes
Profiles on underside	Yes
Mechanical fasteners	HS-22; HS-23; KS

Minimum drum diameter

Z-splice, counter-bending	40 mm / 1.6 in
Stepped overlap splice, counter-bending	40 mm / 1.6 in
Stepped overlap splice, counter-bending	40 mm / 1.6 in
Z-splice, bending	30 mm / 1.2 in

Remarks

Chemical resistance	V
----------------------------	---

The physical data in this data sheet is approximate, can alter depending on production environments and was established at standard ambient conditions (23°C/73°F, 50% relative humidity) in accordance with DIN 50014/ISO 554. Fluctuations in climate can cause variations. See our brochure "Technical Information 1" no. 317 which shows the types of belts that can be supplied and the manufacturing tolerances. Customised types require written confirmation.

Date of last change: 4/3/2023 12:27:15 PM