

Product Data Sheet

PVC150 CG CTxF-NA white



Art. No.: 908761

M 1:2

Applications

Agriculture	Harvesting machines; Processing of fruits and vegetables (not oily and fatty)
General material handling	Horizontal conveying and inclined conveying of small components / bulky goods; Troughed conveyor belt; Tube conveyor belt

Order information

Article number	908761
Suitable for corrugated side walls	No
Belt style	PVC = Interwoven PVC
Standard delivery width	1829 mm / 72.01 in
Longitudinal seam possible	Yes

PVC150 CG CTxF-NA white

Construction

Top face material	Polyvinyl chloride, canners grade
Surface pattern	Crescent top
Coating thickness	5.08 mm / 0.2 in
Color	White
Driving face material	Polyvinyl chloride, canners grade
Surface pattern	Fabric
Coating thickness	0.1 mm / 0.004 in
Color	White
Tension member material	2-ply interwoven fabric of polyester spun warp and weft
Number of fabric plies	1

Technical data

Total thickness	6.6 mm ± 0.33 0.26 in ± 0.013
Weight	5.13 kg/m ² ± 0.26 1.05 lbs/ft ² ± 0.052
k1% value relaxed (effective pull at 1% elongation), established in line with ISO 21181:2005	9.63 N/mm / 55 lbf/in
Recommended Elongation at fitting min.	0.5 %
Recommended Elongation at fitting max.	1.5 %
Rated working tension	26 N/mm / 150 lbf/in at 2 % Elongation
Friction coefficient of driving face against steel panel according ISO 21182	0.45
Permissible operating temperature	-18/82 °C 0/180 °F
Hardness of top face coating as per DIN 53505 (Shore A)	65

PVC150 CG CTxF-NA white

Properties

Lateral stiffness	Laterally flexible
Troughable	Yes
Suitable for accumulation	No
Inclined conveying	Yes
Suitable for knife edges	No
Suitable for curves	No
Flame-retardant	No
Noise development	Normal
Belt support	Support rollers
UV resistance	Normal

Electrostatic properties

Not antistatic	Belt material with electrically insulating properties
-----------------------	---

Fabrication

Suitable for corrugated side walls	No
Profiles on top face	No
Profiles on underside	Yes
Mechanical fasteners	Alligator®RS125; Clipper® G008; Clipper® U2

Minimum drum diameter

Z-splice, counter-bending	89 mm / 3.5 in
Mechanical Alligator® fastener, bending	76 mm / 3 in
Mechanical Clipper® fastener, bending	76 mm / 3 in

Remarks

Chemical resistance	V
----------------------------	---

The physical data in this data sheet is approximate, can alter depending on production environments and was

PVC150 CG CTxF-NA white

established at standard ambient conditions (23°C/73°F, 50% relative humidity) in accordance with DIN 50014/ISO 554. Fluctuations in climate can cause variations.

Date of last change: 10/28/2024 8:40:51 AM